



# Alvium G5

## Alvium G5-510

Alvium G5-510 innovative 5GBASE-T camera with Sony IMX548 CMOS global shutter sensor provides industrial performance for cost effective machine vision applications.

### General

Model	Alvium G5-510
Product series	Alvium G5
Status	Available

### Sensor

Sensor type	Area scan
Chroma	Mono or Color
Spectrum	Visible
Spectral range	300 nm to 1100 nm
Resolution	2,464 × 2,064 (5.10 MP)
Sensor model	Sony IMX548
Sensor architecture (material)	CMOS
Shutter type(s)	Global Shutter
Sensor size	9 mm ø (Type 1/1.8)
Pixel size	2.74 µm × 2.74 µm

### Pixel formats

Sensor bit depth	12-bit
Monochrome pixel formats	Mono8, Mono10, Mono10p, Mono12, Mono12p, Mono12Packed
YUV pixel formats	YCbCr411_8_CbYYCrYY, YCbCr422_8_CbYCrY, YCbCr8_CbYCr
RGB pixel formats	RGB8 (default), BGR8
Bayer pixel formats	BayerRG8, BayerRG10, BayerRG10p, BayerRG12, BayerRG12p, BayerRG12Packed

## Imaging performance

Quantum efficiency @ 529 nm 68 %

## Timing and gain

Max. frame rate 81 fps

## I/Os and power

Non-isolated lines 2 GPIOs (LVTTTL)

Opto-isolated lines 1 input, 1 output

Power supply 10.8 to 26.4 VDC AUX | IEEE 802.3af, Power Class 0 PoE

Power consumption External power: 6.2 W at 12 VDC (typical) | Power over Ethernet: 6.9 W (typical)

## Operating conditions

Operating temperature (housing) -20 °C to 60 °C (housing temperature)

## Mechanical properties

Body dimensions (L x W x H in mm) 60 × 29 × 29

Lens mount(s) C-Mount, CS-Mount, S-Mount

Weight 100 g

## On-board memory and FPGA


Image buffer (RAM) 512 MByte

Non-volatile memory (Flash) 1024 KByte

## Interfaces

Digital interface IEEE 802.3: 5GBASE-T or 2.5GBASE-T (NBASE-T) and 1000BASE-T, IEEE 802.3af Power Class 0 PoE

# Quantum Efficiency



Technical Drawing

