1394

FW-6port-Hub

Hub FireWire 1394a with 6 Ports, Metal Housing

FW-6port-Hub can be used for a 6 Port FireWire 1394a Hub or as a repeater.

With the metal case it is extremely robust and optimal for industrial application.

Highlights

- Compatible with IEEE 1394a
- Up to 400 Mbps
- Easy plug & play, no driver required
- Power plug for optional bus power
- Inclusive power supply (12 V, 1.5 A)
- Compatible with all AVT 1394a cameras
- Compatible with all AVT Software Packages[1]

[1] For details refer to the corresponding releases

ALLIED VISION TECHNOLOGIES GMBH
Taschenweg 2a | D-07646 Stadtroda | Germany
Phone: +49 36428/677-0 | Fax: +49 36428/677-24
www.alliedvisiontec.com | info@alliedvisiontec.com

Technical Specifications

Feature	Description
Ports	6 x 1394a
Speed	Full Duplex Data Rate at 100/200/400 Mbps
OS support	98 SE, Me, 2000, xp, Server 2003, Windows Vista, Linux, MacOS
Compliance	CE, FCC, RoHS
External power	Power Supply 12 V DC, 1.5 A Hub can be powered from 8VDC to 30VDC at 12V Power connector as well at the 12Volt line of the PC connector
Dimensions	150 mm x 70 mm x 30 mm (L x W x H)
Mass	400 g
Operating temperature	+0°C...+50°C

Ordering information:

Hub 6-port 1394a	IEEE1394a 6-port Hub with power supply, metal housing	K0000374

ALLIED VISION TECHNOLOGIES GMBH
Taschenweg 2a | D-07646 Stadtroda | Germany
Phone: +49 36428/677-0 | Fax: +49 36428/677-24
www.alliedvisiontec.com | info@alliedvisiontec.com

Design and specification of the described product(s) are subject to change without notice.

© 03/2008

ALLIED Vision Technologies