Alvium 1800 U

Alvium 1800 U-1240



Alvium 1800 U-1240 innovative USB camera with Sony IMX226 rolling shutter sensor provides industrial performance for cost effective embedded and machine vision applications.

□□	
□□	Alvium 1800 U-1240
□□□□	Alvium 1800 U
□□	Available

□□□	
□□□□□	Area scan
□□	Color, Mono
□□	Visible
□□□□	300 nm to 1100 nm
□□□	4,024 × 3,036 (12.20 MP)
□□□□□	Sony IMX226
□□□□□□□□□	cmos
□□□□	Global Reset Shutter, Rolling shutter (RS)
□□□□□	7.4 × 5.6 mm (9.3 mm, Type 1/1.7)
□□□□	1.85 µm × 1.85 µm

□□□□	
□□□□□□	10-bit
YUV□□□□	YCbCr411_8_CbYYCrYY, YCbCr422_8_CbYCrY, YCbCr8_CbYCr
RGB□□□□	BGR8, RGB8 (default)
□□□□□□	BayerRG12

□□□□	
□□□□ @ 529 nm	74 %

□□□□□

□□□□	35 fps
□□□□	11 µs to 10 s
□□	0.0 dB to 27.0 dB

I/O□□□

□□□□□IO	4 programmable GPIOs
□□□□	Power over USB 3.1 Gen 1 | External power 5.0 V
□□	USB power: 3.1 W (typical) | Ext. power: 3.3 W (typical)

□□□□

□□□□	-20 °C to 65 °C (□□)

□□□□

□□□□□L x W x H mm□	38 × 29 × 29
□□□□	C-Mount, CS-Mount, S-Mount
□□	65 g

□□□□□FPGA

□□□□□RAM□	256 KByte
□□□□□□□□□□□□	1024 KByte

□□

□□□□	usb3.0
□□□□	USB3 Vision

Quantum Efficiency



Technical Drawing

